

Model	PTZ-C-RS2	PTZ-C-RS76	PTZ-C-RS78
Specification	<ul style="list-style-type: none"> <li>◆ Support pelco Matrix</li> <li>◆ Support 4pcs Keyboard linkage, each keyboard can support 32pcs Domes at most</li> <li>◆ Built-In multi-protocols and Optional baud rate</li> <li>◆ OSD Menu, LCD Display, Powerful functions, can be worked with other display and control equipment.</li> <li>◆ Mini and concise appearance, built-in multi-protocols and optional baud rate</li> <li>◆ Can show display the command menu, Protocol, Current Dome ID, Output Monitor ID, Joystick status</li> <li>◆ Built-in multi protocols and baud rate, support all the shortcut key of dome.</li> </ul>	<ul style="list-style-type: none"> <li>◆ support DVR Protocol and kinds of matrix</li> <li>◆ Support 4pcs Keyboard linkage, each keyboard can support 32pcs Domes at most</li> <li>◆ Expediently and comfortably use according to ergonomics design</li> <li>◆ Can show display the command menu, Protocol, Current Dome ID, Output Monitor ID, Joystick status</li> <li>◆ 3-Axis joystick can control the speed dome of Pan /Tilt and Zoom In /Out</li> <li>◆ Built-in multi protocols and baud rate, support all the shortcut key of dome</li> <li>◆ Built-in Multi protocol, easily realize the connection with DVR, Matrix, Picture division equipment, Front-end equipment and others controlling devices</li> <li>◆ Support all the shortcut key of dome</li> <li>◆ Alarm function &amp; shortcut key is available</li> <li>◆ Chinese and English menu can be chosen</li> </ul>	<ul style="list-style-type: none"> <li>◆ Support HDSDI input(:720P/50.720P/60.1080i/50.1080i/60.1080P/25.1080P/30)</li> <li>◆ Support ABS,VGA signal input</li> <li>◆ 8 Inch High definition TFT -LCD Screen Can show the image that returns from the front-end in real time</li> <li>◆ HDSDI/NTSC Image is adjustable automatically, No Manual setting</li> <li>◆ OSD edible menu in Chinese and English can set the kinds of Protocols and it is easy to operate OSD</li> <li>◆ Communication mode: RS232,RS485, RS422,USB2.0</li> <li>◆ Support ABS,VGA signal input 800*600 resolution. And control high speed dome from different factories and mainstream DVR and Pelco matrix.</li> <li>◆ Independet interface Panel and expansively, which can meet the requirement of markets.</li> <li>◆ Extra-Low consumption, 1W for standby mode, foldable structure design can show the best view screen</li> <li>◆ Portable foldable HD visual keyboard, show the camera picture in real time,</li> </ul>

**Parameter**

Display screen	---		8" TFT-LCD
Angle of view for screen	---		0°~135°
Video input	---		composite video (NTSC / PAL ), VGA, HD-SDI
Communication mode	RS485, RS 422	RS232, RS485, RS 422	RS232,RS485,RS422,USB2.0
Communication distance	1200M		
Communication Baud Rate	2400bps,4800bps,9600bps,19200bps		
Control Protocol	PELCO P / D		Pelco P, Pelco D, VISCA,DAHUA,HAIKAN
Power supply	Power supply: DC 9V-12V± 10%		
power consumption	5W		4.2W
Environmental Temperature	-10℃ - +50℃		
Humidity	0-95%, No-Condensation		
Dimenison (mm)	219* 181* 97 ( mm )	377* 160* 98 ( mm )	290* 181* 95mm
Gross weight	1.3KG	2.0KG	1.6Kg

Picture			
---------	---	--	---